



STATE OF ALASKA
DEPARTMENT OF TRANSPORTATION & PUBLIC FACILITIES
STATE EQUIPMENT FLEET HEADQUARTERS
2200 EAST 42ND AVE (RM#311)
ANCHORAGE, ALASKA 99508

AMENDMENT No: ONE (1)

May 20, 2010

INVITATION TO BID: SEF-1560

ITB TITLE: 26,000 GVWR FLATBED TRUCK

BID OPENING DATE & TIME: JUNE 08, 2010 @ 2:30 PM

SECTION III - SPECIFICATIONS:

Specification Item 3.11.3: Delete as written and replace with. "Tires:"

Add New Specification Item: "3.11.3.1 Front Tires: To be three (3) each, including mounted spare, CONTINENTAL HSC or GOODYEAR G288 MSA, 11R22.5, 16PR (LRH) minimum rating, steel belted tubeless radial."

Add New Specification Item: "3.11.3.2 Rear Tires: To be five (5) each, including mounted spare, CONTINENTAL HDL ECO PLUS or CONTINENTAL HDR1 or GOODYEAR G182 RSD, 11R22.5, 16PR (LRH) minimum rating, steel belted tubeless radial."

Add New Specification Item: "3.11.3.3 Spare tires with mounted wheels to be shipped loose."

Add New Specification Item: "4.7.1 The backup alarm is to be permanently wired and mounted to the trucks' frame, not to the flatbed."

Delete Specification Item 7.2.2 entirely.

Delete Specification Items 7.6 through 7.6.5.4 and replace with the following:

"7.6 Electrical:

7.6.1 To include brake controller.

7.6.2 Flood Lighting:

7.6.2.1 To include two (2) each adjustable Par 36 clear halogen flood lights with rubber housings mounted to the top of the headache rack, each being mounted inboard approximately 12 inches to provide light to the bed of the truck.

7.6.2.2 To be separately switched from ignition and include an amber "ON" indicator light.

7.6.3 Strobe Lights:

7.6.3.1 To include two (2) each WHELEN Model L31HAF LED strobe lights mounted on the headache rack/bulkhead of the flatbed body.

7.6.3.2 To be spaced approximately 60 inches apart and the base of the lights are to be approximately six (6) inches above the top of the cab.

7.6.3.3 Wiring is to be a separate 12 gauge wire running with the main wiring for the other rear lighting ending at the same location as the 7-pole plug at the right rear of the frame. The connection shall be *WeatherPack*. Two (2) rocker switches with permanent label is to be provided on the dash to provide "ON/OFF" power and "HIGH/LOW" for the strobe lights mounted on the headache rack/bulkhead"

7.6.4 Stop, Turn, Tail, Back-Up and Clearance Lighting:

7.6.4.1 Wiring, heavy-duty shielded 7-wire, is to be protected from the elements and is to run to two (2) each *POLLACK* #12-707 RV spade type receptacles (or *PHILLIPS* #16-714) located on the rear of the frame area.

7.6.4.2 One (1) receptacle is to be mounted with a mounting bracket on the right curbside rear of the frame for connecting the body's lighting (stop, turn, tail, backup and clearance).

7.6.4.3 The 2nd receptacle is for trailer lighting and brake control. It is to include an additional 30 inches of cable and a mounting bracket. This 2nd receptacle and cable is to be coiled up for installation by the State of Alaska maintenance.

7.6.5 All electrical connections are to include dielectric grease.

Specification Item 8.2.2: Change to read "Truck's frame and flatbed is to be completely painted to inhibit rust."

A signed copy of this amendment must accompany the bid or be received by the STATE EQUIPMENT FLEET, 2200 East 42nd Ave (Rm#316), Anchorage, Alaska 99508, prior to the time set for the opening of the bid.

This amendment consists of three (3) pages.

Cathi Dwyer
(*Signature on original*)
Contracting Officer
(907) 269-0786

Name of Company

Authorized Signature

Date